



SIMATIC DP,BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 90 DEGREE ANGLE CABLE OUTLET, IPCD TECHNOLOGY FAST CONNECT, WITH PG SOCKET 15,8 X 59 X 35,6 MM (WXHxD),

### Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### Interfaces

#### Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

#### Design of the electrical connection

- for network components and terminal equipment

9-pin Sub-D plug

#### Design of the electrical connection / FastConnect

Yes

### Mechanical data

#### Material / of the enclosure

plastic

### Design, dimensions and weight

#### Width

15.8 mm

#### Height

59 mm

#### Depth

35.6 mm

#### Net weight

10 g

### Permitted ambient conditions

#### Ambient temperature

- during operating
- during storage
- during transport

0 °C

-40 ... +70 °C

-40 ... +70 °C

Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
<b>Product properties, functions, components / general</b>	
Product feature / [not supplied - silicon-free]	Yes
Product component	
• PG connection socket	Yes
• strain relief	Yes
<b>Standards, specifications, approvals</b>	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	Yes
<b>letzte Änderung:</b>	Feb 4, 2013